

BUILT BY DATE BUILT PLACED IN SERVICE PURCHASED FROM WHEEL DIA **JOURNALS** MAX. GOVERNED SPEED IDLING SPEED **CYLINDERS BORE** STROKE WT. IN WORKING ORDER WT. ON DRIVERS AIRBRAKE SCHEDULE BRAKE CYLINDERS AIR COMPRESSOR

STEAM GENERATOR OVERNITE HEATER SPARK ARRESTOR

GENERAL MOTORS CORP. E.M.D. DEC. 1953 JAN. 1954 G. M.C. - E.M.D. 40 INCHES HYATT - 6 1 X12 800 R.P.M. 275 R.P.M. 16 8 1 2 10 252000 W/ALL SUPPLIES 252000 6 BL 9 x 8" GARDNER-DENVER MODEL WXO 8015 VAPOR-CLARKSON OK 4625 VAPOR-CLARKSON 4915 AIR-MAZE DIV'N ROCKWELL STD.

GEAR RATIO 62:15 SUPPLIES, TOTAL CAPY. LUBRICATING OIL 200 GALS FUEL OIL 1200 GALS. **BOILER WATER:** FLOOR MOUNTED TANK 820 GALS. HATCH MOUNTED TANK 330 GALS. TOTAL 1150 GALS. SAND 16 CU.FT. MAX. SAFE SPEED 65 M.P.H. MAX.TRACTIVE EFFORT W/ VARIABLE SUPPLIES AT 25% ADHESION 60,500 LBS. MAX. CURVATURE DEGREE 23° MAX.OVERALL DIMENSIONS: **HEIGHT** $15' - 9\frac{1}{2}'$ WIDTH 10-8" TRAIN LENGTH 54-8" ENG. COOLING WATER 235 GALS, 1500 H.P. MODEL FP-7 LEAD UNIT. EQUIPPED WITH DYNAMIC BRAKES. 1957